

Performance Bulletin



Performance Data

Wooldridge Boats 20' SS Drifter OB E-Tec 250hp HO

| RPM | MPH | GPH | MPG |
|------|------|------|-----|
| 500 | 1.8 | 0.2 | 8.0 |
| 1000 | 3.6 | 0.6 | 6.0 |
| 1500 | 5.2 | 1.1 | 4.4 |
| 2000 | 6.3 | 1.8 | 3.4 |
| 2500 | 7.5 | 3.4 | 2.2 |
| 3000 | 9.0 | 6.4 | 1.4 |
| 3500 | 21.3 | 7.8 | 2.7 |
| 4000 | 28.5 | 9.8 | 2.9 |
| 4500 | 33.6 | 12.4 | 2.7 |
| 5000 | 39.1 | 20.5 | 1.9 |
| 5400 | 43.7 | 27.3 | 1.6 |

Note: Data may vary due to changes in the weather, elevation, options and equipment, load or boat bottom conditions. Speed and Fuel data was gathered with an Evinrude fuel management system and Lowrance via NEMA 2000 with a GPS receiver.

Test weight included options, 35 gallons of fuel with safety and test equipment. Total payload of 762 pounds.

Boat: 20' Wooldridge SS Drifter

| | |
|--------------------------------|------------|
| Length | 20'3" |
| Beam | 102" |
| Dry Weight without engine | 1630 lbs. |
| Maximum Horsepower | 250 |
| Fuel Capacity | 50 gal. |
| Weight as Tested - approximate | 2,899 lbs. |

Evinrude 200 HO/140 Jet Power

| | |
|----------------|------------------------------|
| Horsepower | 250 |
| Fuel Induction | ETEC Direct Fuel Injection |
| Displacement | 210 cu. in. |
| Weight | 507 lbs. |
| Gear Ratio | Jet Pump |
| Impeller | Wooldridge 7 5/8" SS 4 Blade |

Test Conditions

| | |
|-------------------|----------|
| Number of persons | 2 |
| Payload | 762 lbs. |
| Air Temperature | 65° |
| Water Temperature | 66° |
| Elevation | 20 ft. |
| Wind Velocity | 0 MPH |