

Performance Bulletin



Performance Data

Wooldridge Boats 23' SS Drifter OB E-Tec 200hp HO

| RPM | MPH | GPH | MPG |
|------|------|-------|------|
| 1000 | 3.1 | .55 | 5.64 |
| 1500 | 4.6 | 1.00 | 4.60 |
| 2000 | 5.8 | 2.01 | 2.89 |
| 2500 | 7.0 | 3.01 | 2.33 |
| 3000 | 9.7 | 4.79 | 2.03 |
| 3500 | 17.3 | 8.33 | 2.08 |
| 4000 | 27.7 | 10.7 | 2.59 |
| 4500 | 32.8 | 14.37 | 2.28 |
| 5000 | 37.6 | 17.74 | 2.12 |
| 5200 | 39.2 | 19.81 | 1.98 |

Note: Data may vary due to changes in the weather, elevation, options and equipment, load or boat bottom conditions. Speed and Fuel data was gathered with an Evinrude fuel management system and Garmin via NEMA 2000 with a GPS receiver.

Test weight included options, 17 gallons of fuel with safety and test equipment. Total payload of 700 pounds.

Boat: 23' Wooldridge SS Drifter

| | |
|-------------------------------|------------|
| Length | 23'3" |
| Beam | 102" |
| Dry Weight without engine | 1,630 lbs. |
| Maximum Horsepower | 250 |
| Fuel Capacity | 52 gal. |
| Weight as Tested- approximate | 2,839 lbs. |

Evinrude 200 HO/140 Jet Power

| | |
|----------------|------------------------------|
| Horsepower | 200 |
| Fuel Induction | ETEC Direct Fuel Injection |
| Displacement | 200 cu. in. |
| Weight | 509 lbs. |
| Gear Ratio | Jet Pump |
| Impeller | Wooldridge 7 5/8" SS 4 Blade |

Test Conditions

| | |
|-------------------|----------|
| Number of persons | 2 |
| Payload | 700 lbs. |
| Air Temperature | 45° |
| Water Temperature | 44° |
| Elevation | 20 ft. |
| Wind Velocity | 1 MPH |