

Performance Bulletin

Aug 2015



Performance Data

Wooldridge Boats

25' Sportster

Etec 250 HO Tiller

RPM	MPH	GPH	MPG
500	1.7	0.2	3.4
1000	3.5	0.5	4.5
1500	4.7	1.1	3.3
2000	6.3	2.0	2.7
2500	7.5	3.1	2.4
3000	11.6	6.3	1.6
3500	18.5	8.0	1.8
4000	26.3	9.3	2.2
4500	31.5	12.8	2.3
5000	37.0	19.9	1.8
5450	40.7	26.7	1.5

-Note: Data may vary due to changes in the weather, elevation, options, equipment, load and boat bottom conditions.

-Speed and Fuel data was gathered using a GPS receiver and averaged from running two directions.

-Test weight included: Options, two men, 60 gallons of fuel, safety and test equipment.

-Total payload of 784 lbs. pounds.

Wooldridge 25' Sportster

Length	25'3"
Beam	102"
Weight as Tested	Aprox. 3350 lbs
Maximum Horsepower	250
Fuel Capacity	97 gal.

Etec 250 HO Tiller

Horsepower	250
Fuel Induction	E-TEC Direct injection
Displacement	210 cu. in.
Weight	455 lbs.
Gear Ratio	1.85:1

Outboard Jet

Impeller	Stainless Steel 4-blade
Diameter/Pitch	Power Jet/ 7-7/8 impeller

Test Conditions

Number of persons	2
Payload	Aprox. 784 lbs.
Air Temperature	58°
Water Temperature	56°
Elevation	20 ft.
Wind Velocity	10 - 15 mph